



PRODUCT-DETAILS

AT34/U119/CSF90/BLB

90D SWL PA66/NPB FTG U119 34MM-BLB



General Information	
Extended Product Type:	AT34/U119/CSF90/BLB
Product ID:	7TCA296170R0575
EAN:	5020963042881
Catalog Description:	90D SWL PA66/NPB FTG U119 34MM-BLB
Long Description:	Adaptalok ATS, 90 Degree Conduit Fitting, Swivel Internal Female Thread, Nominal Conduit Size 34mm, 1-3/16 Inch - 18 Connector UNEF Thread, Polyamide (Nylon) 66, Nickel Plated Brass Thread/TPE, Black with Blue Elastomer
Display Name:	AT34/U119/CSF90/BLB

Additional Information	
Product Main Type:	Adaptaflex Flexible Cable Protection
Application:	For Insertion into Threaded Entries or Knockout to Connect Conduit

Ordering	
EAN:	5020963042881

UPC: 786210257778

Dimensions

Product Net Weight: .143325 lb
65 g

Technical

Number of Batteries: 0
Color: Black/Blue Elastomer
Material: Polyamide/Nylon 6.6
Size: NC 34mm

Environmental

WEEE Category: Product Not in WEEE Scope
RoHS Information: Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Container Information

Package Level 1 Units: 10 piece
Package Level 1 EAN: 5020963042881
Package Level 1 Height: 7.87 in
200 mm
Package Level 1 Depth / Length: 1 in
25 mm
Package Level 1 Width: 7.08 in
180 mm

Certificates and Declarations

Declaration of Conformity - CE: 9AKK107492A9618
RoHS Declaration: 9AKK107992A8994
REACH Declaration: 9AKK107992A8994

External Classifications and Standards

ETIM 8: EC001176 - Screw connection for corrugated plastic hose
ETIM 9: EC001176 - Screw connection for corrugated plastic hose
UNSPSC: 39121311

Categories

Products > Low Voltage Products and Systems > Installation Products > Cable Protection, Explosion Proof and Lighting > Flexible Cable Protection Systems > Adaptaflex Flexible Cable Protection

