


# Terminal control leads, blocks & lug kits



LK75-L



LK75-F



LK... positioning



ATK185



ATK750/3



LD75



LD110

## Ordering details

| For contactors                 | Catalog number |
|--------------------------------|----------------|
| Right and left on A45 ... A75  | LK75-L         |
| Opposite on A45 ... A75        | LK75-F         |
| Right and left on A95 ... A110 | LK110          |

Note: The LK... terminals provided for the A... contactors can be used for the AF, AE, AM, TAE, UA, GA and GAE types.

## Terminal lug kits

| For contactors               | Wire              |          | Tightening torque | Spare terminal hardware included ① | Catalog number         |
|------------------------------|-------------------|----------|-------------------|------------------------------------|------------------------|
|                              | Range             | Capacity | To conductor      |                                    |                        |
| AF145...AF185<br>A145...A185 | 4 AWG...300 MCM   | 1        | 275 in.-lb        | •                                  | ATK185<br>ATK185HK     |
| AF210...AF300<br>A210...A300 | 4 AWG...400 MCM   | 1        | 375 in.-lb        | •                                  | ATK300<br>ATK300HK     |
|                              | 4 AWG...500 MCM   | 2        | 375 in.-lb        | •                                  | ATK300/2<br>ATK300/2HK |
| AF400...AF580                | 2/0 AWG...500 MCM | 2        | 275 in.-lb        | •                                  | ATK580/2<br>ATK580/2HK |
| AF580...AF750                | 2/0 AWG...500 MCM | 3        | 375 in.-lb        | •                                  | ATK750/3<br>ATK750/3HK |
| AF1350                       | 4/0 AWG...500 MCM | 4        | 375 in.-lb        | •                                  | ATK1350/4              |
| AF1350...AF1650              | 1/0 AWG...750 MCM | 4        | 500 in.-lb        | •                                  | ATK1650/4              |
|                              | 1/0 AWG...750 MCM | 6        | 500 in.-lb        | •                                  | ATK1650/6              |

Note: AF1250, AF2050 & AF2650 intended for busbar connection only. Terminal hardware supplied separately. Use of lug kits for AF1350 & AF1650 in general purpose applications reduces the ratings to 1050A and 1350A respectively. Recommend busbar connection for full ratings.

## Spare terminal hardware kits

| For contactors  | Catalog number |
|-----------------|----------------|
| A/F145...A/F185 | LE185          |
| A/F210...A/F300 | LE300          |
| AF400...AF460   | LE460          |
| AF580...AF750   | LE750          |

## Terminal blocks

| For contactors | Catalog number |
|----------------|----------------|
| A45, A75       | LD-75          |
| A95, A110      | LD-110         |

Note: The LD... terminal blocks provided for the A... contactors can be used for the AF, AL, AE, TAL, TAE and UA types.

① Terminal hardware include with A(F)145...AF750 contactors; hardware for AF1350 & AF1650 available only with purchase of lug kit.