Representative Image

## Catalog No. CPL5SA-G

**Description: PVC CTD COND CPLG 5IN ALUM GRAY**

**UPC No 704508362850**

**Home > Cable Protection Systems > Ocal > Electrical conduit coupling**

PVC Coated Conduit Coupling, 5 Inch/129 Metric Coupling Size, 3.37 Inch/85.69 Millimeters Minimum Length of Metal, 7.37 Inch/187.29 Millimeters Total Minimum Length Including Sleeve, Straight Threads, Pressure Sealing Sleeves, Blue Urethane Coating on Interior and Threads, Aluminum, Gray

### Descriptors

| | |
|---|---|
| Category | Electrical conduit coupling |
| Special Features | Pressure-Sealing Sleeves Protect Your Connection |
| Application | Corrosion-Protected Connections for Conduit Sections |

### Specifications

| | |
|---|---|
| Material | Aluminum |
| Color | Gray |

### Classifications

| | |
|---|---|
| Brand Name | Ocal |

### Dimensions

| | |
|---|---|
| Trade Size | 5 in , 129 mm |
| Length | 7.37 in , 187.29 mm |

### Compliance and Certifications

| | |
|---|---|
| RoHS | RoHS3 Compliant |
| REACH | REACH 247 Compliant |
| TSCA | TSCA Section 6(h) Compliant |

| | |
|---|---|
| ETIM | EC000939 Coupler for installation tubes |
| Material | Metal |
| Material quality | Aluminium |
| Surface protection | Untreated |
| Model | Thread |
| For nominal tube diameter | 129 mm |
| Two piece | N |

| | |
|---|---|
| ETIM | EC000939 Coupler for installation tubes |
| With inspection opening and cover | N |