Representative Image

Catalog No. CPO125-5-25

Description: HTSHK THINWALL 1/8IN I.D. GRN 25FT

UPC No 786210775548

Home > Connectivity & Grounding > Shrink-Kon > Heat shrinkable tube

Thin-Wall Heat Shrinkable Tubing, Green Cross-Linked Polyolefin, 1/8 Inch, Shrink Ratio 2:1, Length 25-Foot Reel, Operating Temperature -55 to 135 Degrees Celsius, Non-Lined

Descriptors

Category	Heat shrinkable tube
Special Features	Flame-retardant, cross-linked polyolefin.

Specifications

Shrink Ratio	2:1
Color	Green

Classifications

Brand Name	Shrink-Kon

Dimensions

Thickness	Thin
Length	25 ft

Compliance and Certifications

RoHS	RoHS3 Compliant
REACH	REACH 247 Compliant
TSCA	TSCA Section 6(h) Compliant

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thin-walled
Shrink rate	2:1
Inner diameter before heat-shrink	3.302 mm
Inner diameter before heat-shrink	0.13 inch
Inner diameter after heat-shrink	1.524 mm
Inner diameter after heat-shrink	0.06 inch

ETIM	EC000217 Shrink tubing
Nominal diameter inch	1/8 inch
Wall thickness after shrinking	0.508 mm
Wall thickness after shrinking	0.02 inch
Length	7.62 m
Length	25 ft
Operation temperature	-55-+135 °C
Operation temperature	-67-+275 °F
Colour	Green
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	N
Printable	N
UL approval	Y