Representative Image

## Catalog No. CPO1500-0-C

**Description: HTSHK THINWALL 1-1/2IN ID BLK 100FT**

**UPC No 786210833842**

**Home > Connectivity & Grounding > Shrink-Kon > Heat shrinkable tube**

Thin-Wall Heat Shrinkable Tubing, Black Cross-Linked Polyolefin, 1-1/2 Inch, Shrink Ratio 2:1, Length 100 Feet, Operating Temperature -55 to 135 Degrees Celsius, Non-Lined

### Descriptors

| | |
|---|---|
| Category | Heat shrinkable tube |
| Special Features | Flame-retardant, cross-linked polyolefin. |

### Specifications

| | |
|---|---|
| Voltage Rating | 600 V |
| Color | Black |

### Classifications

| | |
|---|---|
| Brand Name | Shrink-Kon |

### Dimensions

| | |
|---|---|
| Thickness | Thin |
| Length | 100 ft |

### Compliance and Certifications

| | |
|---|---|
| RoHS | RoHS3 Compliant |
| REACH | REACH 247 Compliant |
| TSCA | TSCA Section 6(h) Compliant |

| | |
|---|---|
| ETIM | EC000217 Shrink tubing |
| Type | Heat-shrink |
| Model | Thin-walled |
| Shrink rate | 2:1 |
| Inner diameter before heat-shrink | 38 mm |
| Inner diameter before heat-shrink | 1.5 inch |
| Inner diameter after heat-shrink | 19.05 mm |
| Inner diameter after heat-shrink | 0.75 inch |

| | |
|---|---|
| ETIM | EC000217 Shrink tubing |
| Nominal diameter inch | 1 1/2 inch |
| Wall thickness after shrinking | 1.016 mm |
| Wall thickness after shrinking | 0.04 inch |
| Length | 30.48 m |
| Length | 100 ft |
| Operation temperature | -55-+135 °C |
| Operation temperature | -67-+275 °F |
| Colour | Black |
| Material | Polyolefin (PO-X) |
| Halogen free | N |
| With inner glue | N |
| Printable | N |
| UL approval | Y |