Representative Image

Catalog No. CPO1500-4-C

Description: YELLOW 1.500 THIN-WALL ON 100 FT

UPC No 786209878083

Home > Connectivity & Grounding > Shrink-Kon > Heat shrinkable tube

Thin-Wall Heat Shrinkable Tubing, Yellow Cross-Linked Polyolefin, 1-1/2 Inch, Shrink Ratio 2:1, Length 100 Feet, Operating Temperature -55 to 135 Degrees Celsius, Non-Lined

Descriptors

Category	Heat shrinkable tube

Specifications

Shrink Ratio	2:1
Dielectric Strength	600 V/Mil (24kV/mm)
Volume Resistivity	1016 ohm-cm
Flammability	Flame Retardant
Water Absorption	0.20 %
Color	Yellow

Classifications

Brand Name	Shrink-Kon

Dimensions

Length	100 ft , 30.48 m

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thin-walled
Shrink rate	2:1
Inner diameter before heat-shrink	38 mm
Inner diameter before heat-shrink	1.5 inch
Inner diameter after heat-shrink	19.05 mm
Inner diameter after heat-shrink	0.75 inch
Nominal diameter inch	1 1/2 inch
Wall thickness after shrinking	1.016 mm
Wall thickness after shrinking	0.04 inch
Length	30.48 m

ETIM	EC000217 Shrink tubing
Length	100 ft
Operation temperature	-55-+135 °C
Operation temperature	-67-+275 °F
Colour	Yellow
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	N
Printable	N
UL approval	Y