Representative Image

Catalog No. CPO375-2-C

Description: HTSHK THINWALL 3/8IN I.D. RED 100FT

UPC No 786210834696

Home > Connectivity & Grounding > Shrink-Kon > Heat shrinkable tube

Thin-Wall Heat Shrinkable Tubing, Red Cross-Linked Polyolefin, 3/8 Inch, Shrink Ratio 2:1, Length 100 Feet, Operating Temperature -55 to 135 Degrees Celsius, Non-Lined

Descriptors

Category	Heat shrinkable tube
Special Features	Flame-retardant, cross-linked polyolefin.

Specifications

Shrink Ratio	2:1
Color	Red

Classifications

Brand Name	Shrink-Kon

Dimensions

Thickness	Thin
Length	100 ft

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thin-walled
Shrink rate	2:1
Inner diameter before heat-shrink	9.652 mm
Inner diameter before heat-shrink	0.38 inch
Inner diameter after heat-shrink	4.826 mm
Inner diameter after heat-shrink	0.19 inch
Nominal diameter inch	3/8 inch
Wall thickness after shrinking	0.762 mm
Wall thickness after shrinking	0.03 inch
Length	30.48 m
Length	100 ft
Operation temperature	-55-+135 °C

ETIM	EC000217 Shrink tubing
Operation temperature	-67-+275 °F
Colour	Red
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	N
Printable	N
UL approval	Y