Representative Image

Catalog No. CPO500-0-6

Description: HTSHK THIN WALL 1/2IN I.D. BLK 6IN

UPC No 786210851723

Home > Connectivity & Grounding > Shrink-Kon > Heat shrinkable tube

Thin-Wall Heat Shrinkable Tubing, Black Cross-Linked Polyolefin, 1/2 Inch, Shrink Ratio 2:1, Length 6 Inches, Operating Temperature -55 to 135 Degrees Celsius, Non-Lined

Descriptors

Category	Heat shrinkable tube
Special Features	Flame-retardant, cross-linked polyolefin.

Specifications

Voltage Rating	600 V
Color	Black

Classifications

Brand Name	Shrink-Kon

Dimensions

Thickness	Thin
Length	6 in , 152.4 mm

Compliance and Certifications

RoHS	RoHS3 Compliant
TSCA	TSCA Section 6(h) Compliant
POPs	POPs 28 Compliant

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thin-walled
Shrink rate	2:1
Inner diameter before heat-shrink	12.7 mm
Inner diameter before heat-shrink	0.5 inch
Inner diameter after heat-shrink	6.35 mm
Inner diameter after heat-shrink	0.25 inch

ETIM	EC000217 Shrink tubing
Nominal diameter inch	1/2 inch
Wall thickness after shrinking	0.762 mm
Wall thickness after shrinking	0.03 inch
Length	0.1524 m
Length	0.5 ft
Operation temperature	-55-+135 °C
Operation temperature	-67-+275 °F
Colour	Black
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	N
Printable	N
UL approval	Y

Certification/Standard

CLASS	File Number	Class	CCN	Certificate Number	Library Number
CSA	52390	622302	N/A	N/A	N/A
CSA	702106	903201	N/A	N/A	N/A