Representative Image

Catalog No. CPO63-0-25

Description: HTSHK THINWALL 1/16IN I.D. BLK 25FT

UPC No 786210851044

Home > Connectivity & Grounding > Shrink-Kon > Heat shrinkable tube

Thin-Wall Heat Shrinkable Tubing, Black Cross-Linked Polyolefin, 1/16 Inch, Shrink Ratio 2:1, Length 25-Foot Reel, Operating Temperature -55 to 135 Degrees Celsius, Non-Lined

Descriptors

Category	Heat shrinkable tube
Special Features	Flame-retardant, cross-linked polyolefin.

Specifications

Voltage Rating	600 V
Color	Black

Classifications

Brand Name	Shrink-Kon

Dimensions

Thickness	Thin
Length	25 ft

Compliance and Certifications

RoHS	RoHS3 Compliant
REACH	REACH 240 Compliant
TSCA	TSCA Section 6(h) Compliant
POPs	POPs 28 Compliant

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thin-walled
Shrink rate	2:1
Inner diameter before heat-shrink	1.524 mm
Inner diameter before heat-shrink	0.06 inch
Inner diameter after heat-shrink	0.762 mm

ETIM	EC000217 Shrink tubing
Inner diameter after heat-shrink	0.03 inch
Nominal diameter inch	1/16 inch
Wall thickness after shrinking	0.508 mm
Wall thickness after shrinking	0.02 inch
Length	7.62 m
Length	25 ft
Operation temperature	-55-+135 °C
Operation temperature	-67-+275 °F
Colour	Black
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	N
Printable	N
UL approval	Y

Certification/Standard

CLASS	File Number	Class	CCN	Certificate Number	Library Number
CSA	65789019	903202	N/A	N/A	N/A
CSA	702106	N/A	N/A	N/A	N/A