Representative Image

Catalog No. CPO750-0-A

Description: HTSHK THIN WALL 3/4IN I.D. BLK 4FT

UPC No 786210836331

Home > Connectivity & Grounding > Shrink-Kon > Heat shrinkable tube

Thin-Wall Heat Shrinkable Tubing, Black Cross-Linked Polyolefin, 3/4 Inch, Shrink Ratio 2:1, Length 4 Feet, Operating Temperature -55 to 135 Degrees Celsius, Non-Lined

Descriptors

Category	Heat shrinkable tube
Special Features	Flame-retardant, cross-linked polyolefin.

Specifications

Voltage Rating	600 V
Color	Black

Classifications

Brand Name	Shrink-Kon

Dimensions

Thickness	Thin
Length	4 ft

Compliance and Certifications

REACH	REACH 247 Compliant

ETIM	EC000217 Shrink tubing
Type	Heat-shrink
Model	Thin-walled
Shrink rate	2:1
Inner diameter before heat-shrink	19.05 mm
Inner diameter before heat-shrink	0.75 inch
Inner diameter after heat-shrink	9.652 mm
Inner diameter after heat-shrink	0.38 inch
Nominal diameter inch	3/4 inch
Wall thickness after shrinking	0.762 mm

ETIM	EC000217 Shrink tubing
Wall thickness after shrinking	0.03 inch
Length	1.22 m
Length	4 ft
Operation temperature	-55-+135 °C
Operation temperature	-67-+275 °F
Colour	Black
Material	Polyolefin (PO-X)
Halogen free	N
With inner glue	N
Printable	N
UL approval	Y