Representative Image

Catalog No. CS62

Description: ALUM. COMPRESSION SLEEVE

UPC No 783786100927

Home > Medium Voltage Utility Solutions > Blackburn > Wire or cable compression splice

Aluminum 2 Inch Service Entrance Compression Splice for Wire Range - End A: 12 ASCR, 6 Stranded, 4 Solid, Blue, End B: 1 ASCR, 10 Stranded, 8 Solid, Brown, Die: 5/8. For AL-AL or AL-CU Conductors.

Descriptors

Category	Wire or cable compression splice
Special Features	Constructed from Aluminum for High Conductivity. Solid Center Barriers and large Chamfers for easy cable insertion. Prefilled with Oxide Inhibitor to prevent oxidation and keep out moisture. All Splices are color coded and marked with strip lengths, installation die codes and compression locations, providing easy identification for easy installation.
Application	Basic, uninsulated Splices for Service Entrances. For Combinations of Aluminum-to-Aluminum or Aluminum-to-Copper Conductors.

Specifications

Connection	Compression
Conductor Range	End A: #12 ACSR , #6 STR , #4 SOL End B: #1 ACSR , #10 STR , #8 SOL
Number Of Conductors	2
Material	Aluminum
Insulation	None
Mounting	None
Environmental Conditions	All Seasons / Conditions

Classifications

Brand Name	Blackburn
Standard	RUS Accepted. Complies with ANSI C119.4 when properly installed on Aluminum-to-Aluminum or Aluminum-to-Copper Conductors.

Dimensions

Size	2 Inch

Compliance and Certifications

RoHS	RoHS3 Compliant
REACH	REACH 253 Compliant
TSCA	TSCA Section 6(h) Compliant