



Catalog Number: CTPA12/GR/100M
Product ID: 7TCA298000R0050
EAN Number: 5020963786662
Status: Active

Lightweight Weight, Extra Flexible Conduit, NC Size 12/NW Size 10, Outside Diameter 13.0mm, Inside Diameter 10.1mm, Static Bend Radius 20mm, High Fatigue Life and Abrasion, Impact Resistance, IP40 Rating, Polyamide 6, Reel Length 100 Meters, Grey

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5540 Flexible Non-Metallic Conduit
Brand Name	Harnessflex
Type	Lightweight Conduit
Special Features	Self Extinguishing, Low Smoke Toxicity & Halogen Free
Application	General Purpose, Lightweight Loom Applications
Standard	RoHS, Conforms with end of life vehicle directive (ELV)EU200/53/EC
Trade Size	NC12/NW10
Outside Diameter	13.0mm
Inside Diameter	10.1mm
Length	100 m
Radius	Static Bend Radius 20mm
Flexibility	High
Material	Polyamide/Nylon 6
Color	Gray

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	12mm
Nominal size in inch	5/16 inch
Outer diameter	13mm
Inner diameter	10.1mm
Material	Polyamide 6
Operating temperature	-40-+120°C
Degree of protection (IP)	IP40
Fire resistance in accordance with UL94	HB
UV resistant	Y
Colour	Grey
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	N
Halogen free	Y

Packaging

Inner Quantity	15
Inner Dimensions (inches)	24.5x24.7x50
Outer Quantity	15
Outer Dimensions (inches)	48x40x50

