

Catalog Number:	CTPA20/GR/100M
Product ID:	7TCA298000R0089
EAN Number:	5020963050497
Status:	Active

Lightweight Weight, Extra Flexible Conduit, NC Size 20/NW Size 17, Outside Diameter 21.2mm, Inside Diameter 16.9mm, Static Bend Radius 45mm, High Fatigue Life and Abrasion, Impact Resistance, IP40 Rating, Polyamide 6, Reel Length 100 Meters, Grey

North American Specifications (UNSPSC)

UNSPSC	39131706 Electrical conduit
IGCC	5540 Flexible Non-Metallic Conduit
Brand Name	Harnessflex
Type	Lightweight Conduit
Special Features	Self Extinguishing, Low Smoke Toxicity & Halogen Free
Application	General Purpose, Lightweight Loom Applications
Standard	RoHS, Conforms with end of life vehicle directive (ELV)EU200/53/EC
Trade Size	NC20/NW17
Outside Diameter	21.2mm
Inside Diameter	16..9mm
Length	100 m
Radius	Static Bend Radius 45mm
Flexibility	High
Material	Polyamide/Nylon 6
Color	Gray

European Specifications (ETIM)

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	20mm
Nominal size in inch	1/2 inch
Outer diameter	21.2mm
Inner diameter	16.9mm
Material	Polyamide 6
Operating temperature	-40-+120°C
Degree of protection (IP)	IP40
Fire resistance in accordance with UL94	HB
UV resistant	Y
Colour	Grey
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	N
Halogen free	Y

Packaging

Outer Quantity	15
Outer Dimensions (inches)	1x1x1