Catalog No. CTPA32/100M

Description: 32MM SOLID PA6 CONDUIT 100M - BL

UPC No 5020963027840

Home > Cable Protection Systems > Harnessflex > Flexible Non-Metallic Conduit

Lightweight Weight, Extra Flexible Conduit, NC Size 32/NW Size 29, Outside Diameter 34.5mm, Inside Diameter 28.8mm, Static Bend Radius 55mm, High Fatigue Life and Abrasion, Impact Resistance, IP40 Rating, Polyamide 6, Reel Length 100 Meters, Black

Descriptors

Category	Flexible Non-Metallic Conduit
Special Features	Self Extinguishing, Low Smoke Toxicity & Halogen Free
Application	General Purpose, Lightweight Loom Applications

Specifications

Radius	Static: 55 mm
Flexibility	High
Material	Polyamide/Nylon 6
Color	Black

Classifications

Brand Name	Harnessflex
Standard	RoHS, Conforms with End of Life Vehicle Directive (ELV) EU200/53/EC

Dimensions

Trade Size	NC32/NW29
Outside Diameter	34.5 mm
Inside Diameter	28.8 mm
Length	100 m

Compliance and Certifications

RoHS	RoHS3 Compliant
REACH	REACH 247 Compliant
TSCA	TSCA Section 6(h) Compliant
POPs	POPs 28 Compliant

ETIM	EC001175 Corrugated plastic hose
Nominal diameter	32 mm
Nominal size in inch	1 inch
Outer diameter	34.5 mm
Inner diameter	28.8 mm
Material	Polyamide 6
Degree of protection (IP)	IP40
Fire resistance in accordance with UL94	HB
Bending radius, static	55 mm
UV resistant	Y
Colour	Black
Sheathing material	Not sheathed
Bending strength	Flexible
Lengthwise slotted	N
Halogen free	Y