



PRODUCT-DETAILS

DL020EUN0TGCB2EGU
HAZ3,LED,20KLM,120/277,WALL MNT



General Information

Extended Product Type:	DL020EUN0TGCB2EGU
Product ID:	7TBA022930R0019
Catalog Description:	HAZ3,LED,20KLM,120/277,WALL MNT
Long Description:	Hazlux H3, LED standard housing 20 100 lumens 138W electronic LED driver universal 120 to 277VAC 50/60 Hz standard housing thermal shock-resistant glass globe cast aluminum guard 3/4 inch wall mount Unipak with LED light source grey, Options (certification): US market
Display Name:	DL020EUN0TGCB2EGU

Additional Information

Product Main Type:	Emergency Lighting
Application:	Industrial
Product Type:	Fixture

Ordering

UPC: 786607186605

Dimensions

Product Net Height:	16-3/4 in
Product Net Depth / Length:	14-7/8 in
Product Net Width:	13-3/8 in
Product Net Weight:	21 lb

Technical

Lamp Type:	LED
Number of Batteries:	0
Color:	Grey
Ballast Type:	Standard Housing
Frequency (f):	50/60 Hz
Power Consumption (@P _{cons}):	166 W
Voltage Rating:	120/277 VA °C

Environmental

WEEE Category:	Product Not in WEEE Scope
----------------	---------------------------

Container Information

Package Level 1 Units:	box 1 piece
Package Level 1 EAN:	0786607186605
Package Level 1 Height:	0.254 mm 0.01 in
Package Level 1 Depth / Length:	0.254 mm 0.01 in
Package Level 1 Width:	0.254 mm 0.01 in
Package Level 1 Gross Weight:	21.5 lb

Certificates and Declarations

Data Sheet, Technical Information:	9AKK107680A7169
Instructions and Manuals:	9AKK108468A2729
Declaration of Conformity - CE:	No declaration needed
REACH Declaration:	No declaration needed

External Classifications and Standards	
UNSPSC:	39111612

Categories
Products > Low Voltage Products and Systems > Installation Products > Cable Protection, Explosion Proof and Lighting > Hazardous Lighting & Enclosures

