


- Third generation surface mount design
- Design is based on worldwide telecommunications, data communications, computer peripheral and office automation relay requirements
- High dielectric withstand voltage of 2,000 VAC between coil and contacts (standard type)
- Meets 2.5kV Bellcore surge requirement
- Offers significant board space savings
- European version certified for EN60950/EN41003 Supplementary Insulation at 250 V
- Available in PCB through-hole terminal configuration
- Tape and reel packaging option available



Ordering Information

To Order: Select the part number and add the desired coil voltage rating, (e.g., G6S-2F-DC12).

■ STANDARD VERSION

Terminal	Contact form	Part number			
		Non-latching	Single coil latching	Dual coil latching	High-sensitivity dual coil latching
Gull-wing	DPDT	G6S-2F	G6SU-2F	G6SK-2F	G6SK-2F-H
Inside "L"	DPDT	G6S-2G	G6SU-2G	G6SK-2G	G6SK-2G-H
PCB through-hole	DPDT	G6S-2	G6SU-2	G6SK-2	G6SK-2-H

■ EUROPEAN VERSION

Certified for EN60950/EN41003 Supplementary Insulation at 250 V

Terminal	Contact form	Part number
		Non-latching
Gull-wing	DPDT	G6S-2F-Y
Inside "L"	DPDT	G6S-2G-Y
PCB through-hole	DPDT	G6S-2-Y

Specifications

■ CONTACT DATA

Load	Resistive load (cos ϕ = 1)
Rated load	0.5 A at 125 VAC 2 A at 30 VAC
Contact material	Ag (Au clad)
Max. carry current	2 A
Max. operating voltage	250 VAC, 220 VDC
Max. operating current	2 A
Max. switching capacity	62.5 VA, 60 W
Min. permissible load	10 mVDC, 10 μ A

■ COIL DATA

G6S – Standard non-latching (G6S-2F, G6S-2G, G6S-2)

Rated voltage (VDC)	Rated current (mA)	Coil resistance (Ω)	Pick-up voltage	Dropout voltage	Maximum voltage	Power consumption (mW)
			% of rated voltage			
3	46.7	64.3	75% max.	10% min.	200% max.	140
4.5	31.0	145				
5	28.1	178				
6	23.3	257				
9	15.5	579				
12	11.7	1,028				
24	8.3	2,880	75% max.	10% min.	170% max.	200

G6SU – Standard single coil latching (G6SU-2F, G6SU-2G, G6SU-2)

Rated voltage (VDC)	Rated current (mA)	Coil resistance (Ω)	Set pick-up voltage	Reset pick-up voltage	Maximum voltage	Power consumption (mW)
			% of rated voltage			
3	33.3	90	75% max.	75% max.	180% max.	100
4.5	22.2	203				
5	20.0	250				
6	16.7	360				
9	11.1	810				
12	8.3	1,440	75% max.	75% max.	180% max.	150
24	6.3	3,840				

G6SK – Standard dual coil latching (G6SK-2F, G6SK-2G, G6SK-2)

Set coil			Reset coil		Set pick-up voltage	Reset pick-up voltage	Maximum voltage	Power consumption (mW)
Rated voltage (VDC)	Rated current (mA)	Coil resistance (Ω)	Rated current (mA)	Coil resistance (Ω)				
3	66.6	45	66.6	45	75% max.	75% max.	170% max.	200
4.5	44.4	101	44.4	101				
5	40.0	125	40.0	125				
6	33.3	180	33.3	180				
9	22.2	405	22.2	405				
12	16.7	720	16.7	720	75% max.	75% max.	140% max.	300
24	12.5	1,920	12.5	1,920				

■ COIL DATA (continued)

G6SK – Standard high-sensitivity dual coil latching (G6SK-2F-H, G6SK-2G-H, G6SK-2-H)

Set coil			Reset coil		Set pick-up voltage % of rated voltage	Reset pick-up voltage	Maximum voltage	Power consumption (mW)
Rated voltage (VDC)	Rated current (mA)	Coil resistance (Ω)	Rated current (mA)	Coil resistance (Ω)				
3	46.7	64.3	46.7	64.3	75% max.	75% max.	130% max.	140
4.5	31.0	145	31.0	145				
5	28.1	178	28.1	178				
6	23.3	257	23.3	257				
9	15.6	579	15.6	579				
12	11.7	1,028	11.7	1,028				
24	8.33	2,880	8.33	2,880	75% max.	75% max.	130% max.	200

G6S – European version, non-latching (G6S-2F-Y, G6S-2G-Y, G6S-2-Y)

Rated voltage (DC)	Rated current (mA)	Coil resistance (Ω)	Pick-up voltage	Dropout voltage	Maximum voltage	Power consumption (mW)
			% of rated voltage			
3	66.7	45	75% max.	10% min.	130% max.	200
4.5	44.6	101				
5	40.0	125				
6	33.3	180				
9	22.2	405				
12	16.7	720				
24	9.58	2,504	75% max.	10% min.	110% max.	230

- Note: 1. The rated current and coil resistance are measured at a coil temperature of 23°C (73°F) with a tolerance of $\pm 10\%$.
 2. The operating characteristics are measured at a coil temperature of 23°C (73°F) unless otherwise specified.
 3. Pick-up voltage is measured with no carry current across the contacts.
 4. Pick-up voltage will vary with temperature.


■ CHARACTERISTICS

Contact resistance		75 m Ω max.
Operate (set) time		4 ms max. (mean value approx. 2.5 ms G6S; 2.0 ms G6SU, G6SK)
Release (reset) time		4 ms max. (mean value approx. 1.5 ms G6S; 2.0 ms G6SU, G6SK)
Bounce time		Approx. 0.5 ms
Insulation resistance		1,000 M Ω min. (at 500 VDC)
Dielectric strength		2,000 VAC, 50/60 Hz for 1 minute (G6S, G6SU) between coil and contacts 1,000 VAC, 50/60 Hz for 1 minute (G6SK) between coil and contacts 1,500 VAC, 50/60 Hz for 1 minute between contacts of different poles 1,000 VAC, 50/60 Hz for 1 minute between contacts of same pole
Surge withstand voltage		2,500 V, 2 x 10 μ S (conforms to Bellcore specifications) for G6S and G6SU; 1,500 V, 10 x 160 μ S (conforms to FCC part 68) for G6SK between coil and contacts 2,500 V, 2 x 10 μ S (conforms to Bellcore specs.) between contacts of different poles 1,500 V, 10 x 160 μ S (conforms to FCC part 68) between contacts of same pole
Vibration	Mechanical durability	10 to 55 Hz; 5 mm (0.20 in) double amplitude
	Malfunction durability	10 to 55 Hz; 3.3 mm (0.13 in) double amplitude
Shock	Mechanical durability	1,000 m/s ² ; approx. 100 G
	Malfunction durability	750 m/s ² ; approx. 75 G
Ambient temperature		-40 to +85°C (-40°F + 185°F)
Humidity		35 to 85% RH
Service life	Mechanical	100,000,000 operations min. (at 36,000 operations/hour)
	Electrical	See "Characteristic Data"
Weight		Approx. 2g (0.07 oz)


Note: Data shown are of initial value.

CHARACTERISTIC DATA


Maximum switching capacity





Ambient temperature vs. maximum coil voltage (G6S)




Ambient temperature vs. maximum coil voltage (G6SU, G6SK)



Service Life













Electrical service life



Dielectric strength (Standard version, non-latching)

Detecting current: 1mA




Impulse withstand voltage (Standard version, non-latching)**(2 x 10 μ s)****(10 x 160 μ s)****(10 x 160 μ s)****Impulse withstand voltage (European version)****(10 x 160 μ s)****(10 x 160 μ s)****(2 x 10 μ s)****Dielectric strength (European version, non-latching)****Detecting current: 1mA**

Dimensions


Unit: mm (inch)

■ STANDARD


G6S-2F,
G6S-2F-Y




Terminal arrangement/
Internal connections
(Top view)




Mounting pads
(Top view)




G6S-2G,
G6S-2G-Y




Terminal arrangement/
Internal connections
(Top view)




Mounting pads
(Top view)




G6S-2,
G6S-2-Y



Terminal arrangement/
Internal connections
(Bottom view)




Mounting holes
(Bottom view)




■ SINGLE COIL LATCHING


G6SU-2F




Terminal arrangement/
Internal connections
(Top view)




Mounting pads
(Top view)




G6SU-2G




Terminal arrangement/
Internal connections
(Top view)




Mounting pads
(Top view)




G6SU-2



Terminal arrangement/
Internal connections
(Bottom view)




Mounting holes
(Bottom view)




Unit: mm (inch)

DUAL COIL LATCHING


G6SK-2F,
G6SK-2F-H




Terminal arrangement/
Internal connections
(Top view)




Mounting pads
(Top view)




G6SK-2G,
G6SK-2G-H




Terminal arrangement/
Internal connections
(Top view)




Mounting pads
(Top view)




G6SK-2,
G6SK-2-H



Terminal arrangement/
Internal connections
(Bottom view)



Mounting holes
(Bottom view)



Note: 1. Coplanarity is 0.1 mm max.
2. and indicate mounting orientation marks.