



H5CC-A11F

Timer, plug-in, 11-pin, DIN 48x48 mm, standard type, No-voltage (NPN) input/voltage (PNP) input (switchable), Contact output (time-limit SPDT), 24 to 240 VDC/24 to 240 VAC supply

Specifications

Type	Digital
Installation type	DIN rail, On-panel, Socket
Functions	Multi-functional
Size	1/16 DIN (48 x 48 mm)
Terminal type	Plug-in
Operating mode	Flicker OFF Start (Signal Start), Flicker ON Start (Signal Start), Interval (Signal Start), OFF Delay (Signal), ON Delay (Power ON Start), ON Delay (Signal Start), Signal ON/OFF Delay
Output type	Relay
Contact description	SPDT
Supply voltage AC	24-240 V
Supply voltage DC	24-240 V
Number of pin contact	11
Inputs	Gate (NPN/PNP), Reset (NPN/PNP), Signal (NPN/PNP)
Features	LED

Fits to



P2CF-11-E

Socket, DIN rail/surface mounting, 11-pin, screw terminals

Accessories



P3GA-11

Socket, back-connecting, 11-pin, screw terminals



Y92A-48

Protective cover for DIN48x48mm device, hard plastic (shallow)



Y92A-48F1

Protective cover for DIN 48 x 48 mm timer and counter, soft plastic



Y92A-48G

Protective cover for DIN48x48mm device



Y92F-30

Flush panel mounting adapter for DIN 48x48 mm device



Y92F-45

Panel adaptor, 48 x 48 device into 67 x 67 hole

Downloads

CAD Library



**H5CC
Brochure**

EN PDF 2.01 MB



**H5CC - Digital Timer
Instruction Manual**

EN PDF 2.98 MB



**H5CC Digital Timer
Datasheet**

EN PDF 4.31 MB



**H5CC-AWSD
Instruction Manual**

EN PDF 2.47 MB

