



H7CC-A8D

Digital counter, plug-in, 8-pin, 48x48 mm, IP66, 6 count digits, multifunction: 1-stage & total present counter, SPST 3 A relay output, 12-48 VDC / 24 VAC supply, 12 VDC aux. supply

Specifications

Type	Pre-set counter
Size	1/16 DIN (48 x 48 mm)
Counting functions	1-stage counter, 1-stage counter with total counter
Counting range	-99999 - 999999
LCD backlight	With backlight
Number of digits	6
Body color	Black
Installation type	Socket
Terminal type	Plug-in
Output type	Relay
Relay output	1
Transistor output	0
Inputs	DC voltage, No-voltage
Supply voltage AC	20.4-26.4 V
Supply voltage DC	12-48 V
Speed	10000 Hz
Product Width (unpacked)	48 mm
Product Height (unpacked)	48 mm
Product Depth (unpacked)	63.7 mm

Accessories



P2CF-08-E

Socket, DIN rail/surface mounting, 8-pin, screw terminals



P3G-08

Socket, back-connecting, 8-pin, screw terminals



Y92A-48

Protective cover for DIN48x48mm device, hard plastic (shallow)



Y92A-48F1

Protective cover for DIN 48 x 48 mm timer and counter, soft plastic



Y92F-30

Flush panel mounting adapter for DIN 48x48 mm device



Y92F-45

Panel adaptor, 48 x 48 device into 67 x 67 hole

Downloads

[CAD Library](#)



H7CC Digital Counter/Digital Tachometer

Brochure

EN PDF 3.65 MB



H7CC Digital Counter/Tachometer

Datasheet

EN PDF 16 MB

