



K6CM-ISMA-EIP

Motor Condition Monitoring, AC, 3-phase, Induction motor, Insulation resistance model, 100 to 240 VAC, Transistor control output, Push-in Plus, LCD display, Ethernet IP

Specifications

Supply voltage AC	100-240 V
Applicable motor type	Three-phase induction motor (rated voltage 480 V max.), 0.75 - 7.5kW
Application	Detection of poor insulation
Analysis method	Insulation resistance
Resistance range	0-9.99 Mohm
Number of digital outputs	3
Output type	NPN, Transistor
Product Depth (unpacked)	91.9 mm
Product Width (unpacked)	45 mm
Product Height (unpacked)	90 mm
Communication port(s)	EtherNet/IP
Mounting method	DIN rail
Mounting position	Controller: panel, ZCT: panel (through hole 52 mm diameter)
Setup method	Free software
User interface	Condition monitoring software tool, Front LED, LCD screen

Accessories



K6CM-ISZBI52

ZCT sensor for Insulation Resistance model K6CM-ISM, 200 to 480 VAC, 52mm dia. Through hole

CAD Library



K6CM Datasheet

EN PDF 2.28 MB



K6CM Application Guide Application Guide

EN PDF 16.9 MB



K6CM ISM EIP V1.00 EtherNet/IP EDS file

EN ZIP 3.42 KB



K6CM ISM EIP V2.01 EtherNet/IP EDS file

EN ZIP 3.55 KB



K6CM Motor Condition Monitoring Device Users Manual

EN PDF 19.9 MB



K6CM Motor Condition Monitoring Device Getting Started Guide

EN PDF 3.83 MB



K6CM Motor Condition Monitoring Devices Brochure

EN PDF 5.38 MB



K6CM_SoftwareTool_Function Software

EN ZIP 3.75 MB



Predictive Maintenance Solutions Vol.1 Flyer

EN PDF 4.01 MB



Predictive Maintenance Solutions Vol.2 Flyer

EN PDF 5.93 MB



Predictive Maintenance Solutions Vol.3 Flyer

EN PDF 3.35 MB



Predictive Maintenance Solutions Vol.4 Flyer

EN PDF 7.19 MB



Predictive Maintenance Solutions Vol.5 Flyer

EN PDF 3.96 MB



Predictive Maintenance Solutions Vol.6 Flyer

EN PDF 26.5 MB



Solution case study No.9 Proposal for reduction of plant fire risk

Brochure

EN PDF 542 KB